

## TECHNICAL DATA SHEET

Issue date: 14/10/2025







## Cod. 1092B

Bucket 12 L - Blue

12-litre bucket with external safety release handle, designed with smooth, cavity-free surfaces to ensure total hygiene, easy cleaning and full compliance with the food industry. The rear handle makes emptying easier and lets you hang the bucket on any hook.









## Certifications and regulatory compliance

- Regulation (EC) No 1907/2006 (REACH) and amendments FDA CFR Title 21 and amendments
- Regulation (EU) No 1935/2004 and amendments
- Regulation (EU) No 10/2011 and updates
- Regulation (EU) No 2023/2006 (Good Manufacturing Practices GMP) and amendments

| Conditions of use and safety requirements <sup>1</sup> |   |  |  |
|--|---|--|--|
| Operating temperature                                  | min -20 / max 80 C°  Tested at 65°C according to BS EN 12875-1:2005   |  |  |
| Dishwasher resistance <sup>2</sup>                     |   |  |  |
| Steam sterilization:                                   | Compatible with autoclave cycles at 121°C for 15 minutes according to ISO 17665-1:2006  |  |  |
| Instructions for use:                                  | <ul> <li>Remove all packaging and/or labels.</li> <li>Sanitize/disinfect according to HACCP protocol.</li> <li>Hang the tool using appropriate hooks/supports.</li> <li>Allow to dry completely before use.</li> </ul>  |  |  |
| Signs of deterioration                                 | The product must be regularly inspected. Observable signs of deterioration include:  • Material softening, breakage, or discoloration;  • Detachment of parts or structural damage.  If any such issues are detected, the product must be withdrawn from food contact use and |  |  |
|  | replaced, as also required under Regulation (EU) 2023/988 on general product safety.  |  |  |

| Technical specifications |     |                         |       |  |
|--------------------------|-----|-------------------------|-------|--|
| Length (mm)              | 315 | Material                | PP    |  |
| Width (mm)               | 290 | Net weight (kg)         | 0,825 |  |
| Height (mm)              | 310 | Quantity per pack (pcs) | 6     |  |

<sup>&</sup>lt;sup>1</sup> in accordance with Regulations (EU) 2025/351 and 2023/988

 $<sup>^{2}</sup>$  Exposure to high temperatures or intensive cycles may cause bristle deformation or material degradation.