



**Cod. 1093Y**

Lid for 12 L bucket - Yellow

Lid equipped with integrated hook and positioning guides that ensure a stable fit, reduce the risk of contamination and allow practical, safe use. The innovative marking ensures traceability along the entire supply chain.



**Certifications and regulatory compliance**

- Regulation (EC) No 1907/2006 (REACH) and amendments
- FDA CFR Title 21 and amendments
- Regulation (EU) No 1935/2004 and amendments
- Regulation (EU) No 10/2011 and updates
- Regulation (EU) No 2023/2006 (Good Manufacturing Practices - GMP) and amendments

**Conditions of use and safety requirements<sup>1</sup>**

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating temperature              | min -20 / max 80 C°                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Dishwasher resistance <sup>2</sup> | Tested at 65°C according to BS EN 12875-1:2005                                                                                                                                                                                                                                                                                                                                                                                           |
| Steam sterilization:               | Compatible with autoclave cycles at 121°C for 15 minutes according to ISO 17665-1:2006                                                                                                                                                                                                                                                                                                                                                   |
| Instructions for use:              | <ul style="list-style-type: none"> <li>• Remove all packaging and/or labels.</li> <li>• Sanitize/disinfect according to HACCP protocol.</li> <li>• Hang the tool using appropriate hooks/supports.</li> <li>• Allow to dry completely before use.</li> </ul>                                                                                                                                                                             |
| Signs of deterioration             | <p>The product must be regularly inspected. Observable signs of deterioration include:</p> <ul style="list-style-type: none"> <li>• Material softening, breakage, or discoloration;</li> <li>• Detachment of parts or structural damage.</li> </ul> <p>If any such issues are detected, the product must be withdrawn from food contact use and replaced, as also required under Regulation (EU) 2023/988 on general product safety.</p> |

**Technical specifications**

|             |     |                         |      |
|-------------|-----|-------------------------|------|
| Length (mm) | 290 | Material                | PP   |
| Width (mm)  | 320 | Net weight (kg)         | 0,19 |
| Height (mm) | 35  | Quantity per pack (pcs) | 6    |

<sup>1</sup> in accordance with Regulations (EU) 2025/351 and 2023/988

<sup>2</sup> Exposure to high temperatures or intensive cycles may cause bristle deformation or material degradation.