



Issue date: 25/02/2026



Cod. 1095K

Aluminium handle 60 cm Ø 25 mm - Black

Light and resistant aluminium handle, equipped with an ergonomic plastic knob with a hole for hanging and a non-slip finish, which guarantees a firm and comfortable grip. Complete with Italian thread for use with compatible tools.



Certifications and regulatory compliance

- Regulation (EC) No 1907/2006 (REACH) and updates
- FDA CFR Title 21 and amendments
- Regulation (EU) No 1935/2004 and amendments
- Regulation (EU) No 10/2011 and amendments
- Regulation (EU) No 2023/2006 (Good Manufacturing Practices GMP) and amendments

Conditions of use and safety requirements¹

Operating temperature	min -20 / max 80 C°
Dishwasher resistance ²	-
Steam sterilization	Compatible with autoclave cycles at 121°C for 15 minutes according to ISO 17665-1:2006
Instructions for use	<ul style="list-style-type: none"> • Remove all packaging and/or labels. • Sanitize/disinfect according to HACCP protocol. • Hang the tool using appropriate hooks/supports. • Allow to dry completely before use.
Signs of deterioration	<p>The product must be regularly inspected. Observable signs of deterioration include:</p> <ul style="list-style-type: none"> • Material softening, breakage, or discoloration; • Detachment of parts or structural damage. <p>If any such issues are detected, the product must be withdrawn from food contact use and replaced, as also required under Regulation (EU) 2023/988 on general product safety.</p>

Technical specifications

Length (mm)	600	Material	PP - AL
Width (mm)	-	Net weight (kg)	0,15
Height (mm)	-	Quantity per pack (pcs)	10
Diameter (mm)	25		

¹ in accordance with Regulations (EU) 2025/351 and 2023/988

² Exposure to high temperatures or intensive cycles may cause bristle deformation or material degradation.